

VHF CL RADOME ANTENNAS

- radome with high thickness epoxy resin
- conical whip to reduce the wind impact
- resistant to 1 inch ice
- stainless steel bracket
- TETRA Service Frequency

Code	Frequency	gain	V irradiation	Antenna type	Max power	Lenght	radom dia	Weight	Load wind 150 km/h
10080	70-75 Mhz	2 dbi	78°	Dipole	100 W	2,80 mt	28 mm	4,0 kg	100 N
10081	75-80 Mhz	2 dbi	78°	Dipole	100 W	2,80 mt	28 mm	4,0 Kg	100 N
10098-1	118-136 Mhz	2 dbi	78°	Dipole	100 W	1,70 mt	21 mm	3,5 Kg	60 N
10082	136-145 Mhz	2 dbi	78°	Dipole	50 W	1,50 mt	21 mm	3,0 Kg	50 N
10099-1	144 - 162 Mhz	2 dbi	78°	Dipole	50 W	1,30 mt	21 mm	2,0 Kg	43 N
10083	155-175 Mhz	2 dbi	78°	Dipole	50 W	1,30 mt	21 mm	2,0 kg	43 N
10084	136-150 Mhz	5 dbi	30°	2 el. Collinear	200 W	2,70 mt	28 mm	5,5 Kg	120 N
10097-1	147-162 Mhz	5 dbi	30°	2 el. Collinear	200 W	2,50 mt	28 mm	5,0 Kg	120 N
10085	160-175 Mhz	5 dbi	30°	2 el. Collinear	200 W	2,50 mt	28 mm	5,0 Kg	120 N

MECHANICAL FEATURES

Length	see the table
Weight	see the table
Sections	1
Radome	epoxy fiberglass
Fitting	See the drawing
Brackets material	Aisi 316 stainless Steel
Structure	Epoxy fiberglass
Finishing	Polyurethane paint
Colour	White RAL 9000 Grey RAL 7001
Irradiation element material	Brass
Working temperature	-35°C +80°C
Max wind resistance	150 Km/h
Base torsion force	see the table

ELECTRICAL FEATURES

Frequency	see the table
Antenna	see the table
S.W.R.	< 1,5
Impedance	50 Ohm
Gain	see the table
Power	See the table
Polarization	Vertical
Horizontal irradiation	360°
Vertical irradiation	see the table
Connector	N female PL female (page 34)
Lightning protection	Yes
DC closed	Yes

ENVIRONMENTAL SPECIFICATION

Temperature, salt, ice, sun irradiation resistance in accordance with MIL-STD 810E
 Vibration resistance in accordance with MIL-STD 167-1
 Shock resistance in accordance with MIL-STD 810E
 Treatments and paintings in accordance with MIL-T-704K

